



ZINGFA R404A (LBP) HERMETİK KOMPRESÖRLER TEKNİK BİLGİLERİ

Models	Displacement (cm3)		REFRIGERATION CAPACITY AT 50 Hz rated 50HZ / 54.5 °C / Watt Evaporating Temperature									
	Weight (KG)		Oil Charge (cm3)	Power source	-40 ° C	-35 ° C	-30 ° C	-23,3 ° C	-20 ° C	-10 ° C	0 ° C	
QL 52	52	33	1500	220-240V/1 /50HZ 208-230V/1 /60HZ	475*	836	1.410	2.481	3.037	5.050	5.300	
QL 62	62,7	35			1136*	1.286	1.993	3.140	3.660	6.130	6.300	
QL3 - 52	52	31	1500	220V/3/60HZ 380V/3/50HZ 380V/3/60HZ 460V/3/60HZ	475*	836	1.410	2.481	3.037	5.050	5.300	
QL3 - 74	74,2	32			1404*	1.521	2.358	3.661	4.333	7.265	7.330	
QL3 - 112	112,5	46	2000	220V/3/60HZ 380V/3/50HZ 380V/3/60HZ 460V/3/60HZ	1646*	2.035	3.164	5.238	6.231	10.550	10.600	
QL3 - 134	134,8	46			2354*	2.782	4.177	6.514	7.892	12.120	12.630	

Condensing Temp Range <65 °C

Compressor Internal Protectors: Internal Motor Protector and Pressure Relief Valve

To obtain refrigeration capacity at 60Hz, multiply its values at 50Hz by 1.2

*Condensing Temp: 50 °C

